## LITHIUM CELLS OR BATTERIES TEST SUMMARY AND CERTIFICATION IN ACCORDANCE WITH SUB-SECTION 38.3 OF MANUAL OF TESTS AND CRITERIA

## **BATTERY TRANSPORTION INFORMATION**

Name of cell, battery or product manufacture, as applicable:			Cell, battery or product manufacturer's contact information to include address, phone				
Item Name Model name : CR17335A WK11		nı	number, email address and website for more information:				
Internal cell: CR17335A							
Normal voltage 3V			Maxell, Ltd.				
Rated capacity 1650mAh			5 Takumidai, Ono-Shi, Hyogo, 675-1322 Japan Phone: (+81) 794-63-8054				
Item Description Lithium metal cell / battery			e-mail: md_tech_support@maxell.co.jp				
			Web: https://www.maxell.co.jp				
Name of the test laboratory to include address, phone number, email address and website for more information		Test report identification number:				Date of the test report:	
email address and website for more information		C1908-8				December 2, 2019	
Maxell, Ltd.							
1 Koizumi, Oyamazaki, Oyamazaki-cho, Otokuni-gun, Kyoto,		Li	List of test conducted and results(i.e. Pass/Fail)				
618-8525 Japan						Ī	
Phone: (+81) 75-956-4148 e-mail: md_tech_support@maxell.co.jp			Test number	Designation	Results		
Web: https://www.maxell.co.jp				· · <del>g</del> · · - · · · · ·			
, , , , , , , , , , , , , , , , , , ,			T-1	Altitude Simulation	Pass		
			1-1	Allitude Olimulation	1 433		
Description of cell or battery to include at a minimum: Lithium ion or Lithium metal cell or battery Mass; Watt-hour rating, or Lithium content, Physical description of the cell/battery; and Model Number			T-2	Thermal Test	Pass		
			T-3	Vibration	Pass		
Cell / battery Type : Lithium n	netal		T-4	Shock	Pass		
			1-4	SHOCK	F d 5 5		
Cell or Battery Cell (Single cell battery			T-5	External short circuit	Pass		
Lithium content : <b>0.6g</b>							
			T-6	Impact / Crush	Pass		
Cell or Battery Weight : 18.5g			T-7	Overcharge *	Not applicable		
Physical description : <b>Cylindrical type</b>					. tet appneasie		
			T-8	Forced Discharge	Pass		
			* Only secondary battery with protection element				
Reference to assembled battery testing Reference to the revised			d edition of the Manual of Tests and For air transport only: D			oes the cell or hattery	
requirements, if applicable(i.e. 38.3.3 (f) Criteria used and to ame					comply with the 30% State of Charge?		
and 38.3.3 (g))							
Not applicable Revision 6, Amendment		t 1			Not applicable		
PRODUCT CLASSIFICATION FOR TRANSPORT(According to UN-DGP)							
,			Proper Shipping Name:				
UN3090			Lithium Metal Batteries				
Signature with name and title of signatory as an indication of the							
validity information provided.		Tł	This document remains valid as long as no changes, modifications or additions are made				
Keisuke Kawabe / Senior Manager, MD Engineering Departme			to the model(s) described in this document, after being transported from a Manufacturer				
Signature			MAXELL, LTD. The model(s) has(have) been classified according to the applicable transport regulations and the UN Manual of Tests and Criteria as of the date of the				
K Karaha			certification. The model(s) must be packaged, labeled and documented according to				
- I VI VI VI VIVI		CC	country and other international regulations for transportation.				
Phone: (+81) 794-63-8054							
e-mail: md_tech_support@maxell.co.jp							
Date document was generated		4					
Date document was generated							