LITHIUM CELLS OR BATTERIES TEST SUMMARY AND CERTIFICATION IN ACCORDANCE WITH SUB-SECTION 38.3 OF MANUAL OF TESTS AND CRITERIA

BATTERY TRANSPORTION INFORMATION

Name of cell, battery or product manufacture, as applicable:			Cell, battery or product manufacturer's contact information to include address, phone				
Maria Nama Mandal managa (DDCC)		nu	number, email address and website for more information:				
Item Name Model name : CR2016							
Normal voltage 3V			Mayall Ltd				
S .			Maxell, Ltd. 5 Takumidai, Ono-Shi, Hyogo, 675-1322 Japan				
Rated capacity 90mAh			5 Takumidai, Ono-Sni, Hyogo, 675-1322 Japan Phone: (+81) 794-63-8054				
Item Description Lithium metal cell / battery			e-mail: md_tech_support@maxell.co.jp				
Littlan metal cen / battery			Web: https://www.maxell.co.jp				
			, in the second				
Name of the Acad leb condensate in the decade and acad management		Τ.	-4 4 !-1	4:6: 4:		Data af the standard and	
Name of the test laboratory to include address, phone number, email address and website for more information		Test report identification number:			Date of the test report:		
email address and website for more information		C-1804-5			May 30, 2018		
Maxell, Ltd.							
1 Koizumi, Oyamazaki, Oyamazaki-cho, Otokuni-gun, Kyoto,		List of test conducted and results(i.e. Pass/Fail)					
618-8525 Japan							
Phone: (+81) 75-956-4148							
e-mail: md_tech_support@maxell.co.jp			Test number	Designation	Results		
Web: https://www.maxell.co.jp							
			T-1	Altitude Simulation	Pass		
			1-1	/ unitage Officialion	1 000	<u> </u>	
Description of cell or battery to include at a minimum: Lithium ion or			T-2	Thermal Test	Pass		
Lithium metal cell or battery Mass; Watt-hour rating, or Lithium			1-2	rnermai rest	Pass		
content, Physical description of the cell/battery; and Model Number			т 2	Vibration	Dage		
			T-3	Vibration	Pass		
Cell / battery Type : Lithium n	netal		T 4	OhI	D	Ī	
			T-4	Shock	Pass		
Cell or Battery Cell			Т.	External about aircuit	Dage	1	
			T-5	External short circuit	Pass		
Lithium content : 0.03g			т.с	loon and I Count	D	Ī	
			T-6	Impact / Crush	Pass		
Cell or Battery Weight : 1.7g						1	
Physical description : Coin type			T-7	Overcharge *	Not applicable		
					_	†	
			T-8	Forced Discharge	Pass		
			* Only secondary battery with protection element				
Reference to assembled battery testing requirements, if applicable(i.e. 38.3.3 (f) and 38.3.3 (g))					For air transport only: Does the cell or battery comply with the 30% State of Charge?		
			illellis illeleit	o, ii aliy.			
and 00.0.0 (g))							
Not applicable Revision 6					Not applicable		
PRODUCT CLASSIFICATION FOR TRANSPORT(According to UN-DGP)							
UN Classification, Proper Shipping Name:							
LINGOOO			Lithium Matal Dattania				
UN3090			Lithium Metal Batteries				
Signature with name and title of signatory as an indication of the			-				
validity information provided. Keisuke Kawabe / Senior Manager, MD Engineering Department Signature		Th	This document remains valid as long as no changes, modifications or additions are made to the model(s) described in this document, after being transported from a Manufacturer MAXELL, LTD. The model(s) has(have) been classified according to the applicable transport regulations and the UN Manual of Tests and Criteria as of the date of the				
		_					
		tra					
K. Kawahe			certification. The model(s) must be packaged, labeled and documented according to				
1 . 1 a wave		СО	country and other international regulations for transportation.				
Phone: (+81) 794-63-8054							
e-mail: md_tech_support@maxell.co.jp							
Date document was generated							
-							
January 1, 2025							