January 1, 2025

LITHIUM CELLS OR BATTERIES TEST SUMMARY AND CERTIFICATION IN ACCORDANCE WITH SUB-SECTION 38.3 OF MANUAL OF TESTS AND CRITERIA

BATTERY TRANSPORTION INFORMATION

| Name of cell, battery or product manufacture, as applicable: | | Cell, battery or product manufacturer's contact information to include address, phone | | | | | |
|---|--|--|---|------------------------|---|--------------------------|--|
| Item Name Model name : CR2032HRS HAB-T69 | | number, email address and website for more information: | | | | | |
| Internal cell: CR2032HRS Normal voltage 3V | | Maxell, Ltd. | | | | | |
| Rated capacity 200mAh | | | 5 Takumidai, Ono-Shi, Hyogo, 675-1322 Japan | | | | |
| Item Description Lithium metal cell / battery | | Phone: (+81) 794-63-8054 e-mail: md_tech_support@maxell.co.jp | | | | | |
| - | | Web: https://www.maxell.co.jp | | | | | |
| | | | | | | | |
| Name of the test laboratory to include address, phone number, | | Test report identification number: | | | | Date of the test report: | |
| email address and website for more information | | C-2011-1 | | | | December 18, 2020 | |
| Maxell, Ltd. 1 Koizumi, Oyamazaki, Oyamazaki-cho, Otokuni-gun, Kyoto, | | List of test conducted and results(i.e. Pass/Fail) | | | | | |
| 618-8525 Japan | | and the second s | | | | | |
| Phone: (+81) 75-956-4148 e-mail: md_tech_support@maxell.co.jp | | | Test number | Designation | Results | | |
| Web: https://www.maxell.co.jp | | | | | | | |
| | | | T-1 | Altitude Simulation | Pass | | |
| Description of cell or battery to include at a minimum: Lithium ion or Lithium metal cell or battery Mass; Watt-hour rating, or Lithium content, Physical description of the cell/battery; and Model Number | | | T-2 | Thermal Test | Pass | | |
| | | | T-3 | Vibration | Pass | | |
| Cell / battery Type : Lithium metal | | | T-4 | Shock | Pass | | |
| Cell or Battery Cell (Single cell battery) | | | T-5 | External short circuit | Pass | | |
| Lithium content : 0.06g | | | T-6 | Impact / Crush | Pass | | |
| Cell or Battery Weight : 3.3g Physical description : Coin type | | | T-7 | Overcharge * | Not applicable | | |
| | | | T-8 | Forced Discharge | Pass | | |
| | | * Only secondary battery with protection element | | | | | |
| Reference to assembled battery testing requirements, if applicable(i.e. 38.3.3 (f) and 38.3.3 (g)) | | | | | For air transport only: Does the cell or battery comply with the 30% State of Charge? | | |
| Not applicable Revision 6, Amendment | | | | | Not applicable | | |
| | | | | | | | |
| PRODUCT CLASSIFICATION FOR TRANSPORT(According to UN-DGP) | | | | | | | |
| | | | | Proper Shipping Name: | | | |
| UN3090 | | Lithium Metal Batteries | | | | | |
| Signature with name and title of signatory as an indication of the validity information provided. | | | 'his document romains valid as long as no changes, modifications or additions are made | | | | |
| Keisuke Kawabe / Senior Manager, MD Engineering Departme Signature | | to | This document remains valid as long as no changes, modifications or additions are made to the model(s) described in this document, after being transported from a Manufacturer | | | | |
| | | tra | MAXELL, LTD. The model(s) has(have) been classified according to the applicable transport regulations and the UN Manual of Tests and Criteria as of the date of the certification. The model(s) must be packaged, labeled and documented according to country and other international regulations for transportation. | | | | |
| K. Kawahe | | | | | | | |
| Phone: (+81) 794-63-8054 | | | | | | | |
| e-mail: md_tech_support@maxell.co.jp | | | | | | | |
| Date document was generated | | | | | | | |