S250101-5

| LITHIUM CELLS OR BATTERIES TEST SUMMARY AND CERTIFICATION<br>IN ACCORDANCE WITH SUB-SECTION 38.3<br>OF MANUAL OF TESTS AND CRITERIA   |  |  |  |   |   |  |  |
|---|--|--|--|---|---|--|--|
| BATTERY TRANSPORTION INFORMATION  |  |  |  |   |   |  |  |
| Name of cell, battery or product manufacture, as applicable:<br>Item Name Model name : CR2450HR WK<br>Internal cell : CR2450HR<br>Normal voltage 3V<br>Rated capacity 550mAh<br>Item Description Lithium metal cell / battery |  | Cell, battery or product manufacturer's contact information to include address, phone<br>number, email address and website for more information:<br>Maxell, Ltd.<br>5 Takumidai, Ono-Shi, Hyogo, 675-1322 Japan<br>Phone: (+81) 794-63-8054<br>e-mail: md_tech_support@maxell.co.jp<br>Web: https://www.maxell.co.jp |  |   |   |  |  |
| Name of the test laboratory to include address, phone number,<br>email address and website for more information<br>Maxell, Ltd.<br>1 Koizumi, Oyamazaki, Oyamazaki-cho, Otokuni-gun, Kyoto,                                   |  |  | Test report identification number:<br>C-1910-13<br>List of test conducted and results(i.e. Pass/Fail)  |   |   | Date of the test report:<br>October 15, 2019 |  |
| 618-8525 Japan<br>Phone: (+81) 75-956-4148<br>e-mail: md_tech_support@maxell.co.jp<br>Web: https://www.maxell.co.jp   |  |  | Test number  |   | Results   |  |  |
| Description of cell or battery to include at a minimum: Lithium ion or<br>Lithium metal cell or battery Mass; Watt-hour rating, or Lithium<br>content, Physical description of the cell/battery; and Model Number             |  | _  | T-2  | Thermal Test                                    | Pass  | -  |  |
| Cell / battery Type : Lithium metal   |  |  | T-3<br>T-4   | Vibration                                       | Pass<br>Pass  | -  |  |
| Cell or Battery Cell (Single cell battery)  |  |  | T-5  | External short circuit                          | Pass  |  |  |
| Lithium content : 0.15g Cell or Battery Weight : 7.4g   |  |  | T-6  | Impact / Crush                                  | Pass  | -  |  |
| Physical description : Coin type  |  |  | T-7<br>T-8   | Overcharge * Forced Discharge                   | Not applicable<br>Pass  | -  |  |
|   |  |  |  | * Only secondary batte                          | ry with protection eleme  | L<br>ent                                     |  |
| Reference to assembled battery testing<br>requirements, if applicable(i.e. 38.3.3 (f)<br>and 38.3.3 (g))  |  |  |  |   | For air transport only: Does the cell or battery comply with the 30% State of Charge? |  |  |
| Not applicable Revision 6, Amendment  |  |  |  |   | Not applicable  |  |  |
|   |  |  |  | I FOR TRANSPORT(According to UN-DGP)            |   |  |  |
|   |  |  |  | roper Shipping Name:<br>Lithium Metal Batteries |   |  |  |
| Keisuke Kawabe / Senior Manager, MD Engineering Departme<br>Signature   |  |  | This document remains valid as long as no changes, modifications or additions are made to the model(s) described in this document, after being transported from a Manufacturer MAXELL, LTD. The model(s) has(have) been classified according to the applicable transport regulations and the UN Manual of Tests and Criteria as of the date of the certification. The model(s) must be packaged, labeled and documented according to country and other international regulations for transportation. |   |   |  |  |
| Phone: (+81) 794-63-8054<br>e-mail: md_tech_support@maxell.co.jp<br>Date document was generated   |  |  |  |   |   |  |  |
| January 1, 2025   |  |  |  |   |   |  |  |