LITHIUM CELLS OR BATTERIES TEST SUMMARY AND CERTIFICATION IN ACCORDANCE WITH SUB-SECTION 38.3 OF MANUAL OF TESTS AND CRITERIA

BATTERY TRANSPORTION INFORMATION

| Name of cell, battery or product manufacture, as applicable: | | С | Cell, battery or product manufacturer's contact information to include address, phone | | | | |
|---|-------|--|--|-----------------------------|--------------------------------------|--|--|
| | | | number, email address and website for more information: | | | | |
| Internal cell: ML2016 H | | | | | | | |
| Normal voltage 3V | | | Maxell, Ltd. | | | | |
| Rated capacity 30mAh | | | 5 Takumidai, Ono-Shi, Hyogo, 675-1322 Japan Phone: (+81) 794-63-8054 | | | | |
| Item Description Lithium metal cell / battery | | e-mail: md_tech_support@maxell.co.jp | | | | | |
| | | | Web: https://www.maxell.co.jp | | | | |
| | | | | | | | |
| Name of the death labour to include a delegation of the second | | Took speed identification pumbers | | | | | |
| Name of the test laboratory to include address, phone number, email address and website for more information | | Test report identification number: M-2206-01 | | | | Date of the test report: September 27, 2022 | |
| Maxell, Ltd. | | September 27, 2022 | | | | | |
| махен, ьто. 1 Koizumi, Oyamazaki, Oyamazaki-cho, Otokuni-gun, Kyoto, | | List of test conducted and results(i.e. Pass/Fail) | | | | | |
| 618-8525 Japan | | , | | | | | |
| Phone: (+81) 75-956-4148 | | | T4 | Danima etian | Danita | | |
| e-mail: md_tech_support@maxell.co.jp Web: https://www.maxell.co.jp | | | Test number | Designation | Results | | |
| . пцв.личи.пихан.водр | | | T-1 | Altitude Simulation | Pass | | |
| | | | 1-1 | Altitude Simulation | F d 5 5 | | |
| Description of cell or battery to include at a minimum: Lithium ion or Lithium metal cell or battery Mass; Watt-hour rating, or Lithium content, Physical description of the cell/battery; and Model Number | | | T-2 | Thermal Test | Pass | | |
| | | | T-3 | Vibration | Pass | | |
| Cell / battery Type : Lithium n | netal | | T-4 | Shock | Pass | | |
| Cell or Battery Lithium content : 0.015g Cell or Battery Weight : 2.2g | | | T-5 | External short circuit | Pass | | |
| | | | T-6 | Impact / Crush | Pass | | |
| | | | T-7 | Overcharge * | Not applicable | | |
| Physical description : Coin type | | | T-8 | Forced Discharge | Pass | | |
| | | | * Only secondary battery with protection element | | | | |
| Reference to assembled battery testing Reference to the revised | | | edition of the Manual of Tests and For air transport only: Does the | | | oes the cell or hattery | |
| requirements, if applicable(i.e. 38.3.3 (f) and 38.3.3 (g)) | | | | | comply with the 30% State of Charge? | | |
| Not applicable Revision 7 | | | | | Not applicable | | |
| . tericon , | | | | | '' | | |
| PRODUCT CLASSIFICATION FOR TRANSPORT(According to UN-DGP) | | | | | | | |
| | | | Proper Shipping Name: | | | | |
| UN3090 | | | Lithium Metal Batteries | | | | |
| Signature with name and title of signatory as an indication of the validity information provided. | | T٢ | This document remains valid as long as no changes, modifications or additions are made | | | | |
| · | | to | to the model(s) described in this document, after being transported from a Manufacturer | | | | |
| Signature K Co. co. l | | | MAXELL, LTD. The model(s) has(have) been classified according to the applicable transport regulations and the UN Manual of Tests and Criteria as of the date of the | | | | |
| | | се | certification. The model(s) must be packaged, labeled and documented according to country and other international regulations for transportation. | | | | |
| | | 00 | ranay and offi | or international regulation | ono ioi tianoportation. | | |
| Phone: (+81) 794-63-8054 e-mail: md_tech_support@maxell.co.jp | | | | | | | |
| · · · · · · · · · · · · · · · · · · · | | | | | | | |
| Date document was generated | | ĺ | | | | | |
| January 1, 2025 | | | | | | | |