LITHIUM CELLS OR BATTERIES TEST SUMMARY AND CERTIFICATION IN ACCORDANCE WITH SUB-SECTION 38.3 OF MANUAL OF TESTS AND CRITERIA

BATTERY TRANSPORTION INFORMATION

| Name of cell, battery or product manufacture, as applicable: | | Cell, battery or product manufacturer's contact information to include address, phone | | | | | |
|---|-------|---|---|------------------------|--|------------------|--|
| Item Name Model name : ML2032 T26 | | nu | number, email address and website for more information: | | | | |
| Internal cell: ML2032 | | | | | | | |
| Normal voltage 3V | | | Maxell, Ltd. | | | | |
| Rated capacity 65mAh | | | 5 Takumidai, Ono-Shi, Hyogo, 675-1322 Japan Phone: (+81) 794-63-8054 | | | | |
| Item Description Lithium metal cell / battery | | | e-mail: md_tech_support@maxell.co.jp | | | | |
| , | | | Web: https://www.maxell.co.jp | | | | |
| | | | | | | | |
| | | | | | | | |
| Name of the test laboratory to include address, phone number, email address and website for more information | | Test report identification number: | | | Date of the test report: | | |
| emaii auuress anu wedsite idi midre imidination | | M-1910-3 | | | | October 15, 2019 | |
| Maxell, Ltd. | | | | | | | |
| 1 Koizumi, Oyamazaki, Oyamazaki-cho, Otokuni-gun, Kyoto, | | List of test conducted and results(i.e. Pass/Fail) | | | | | |
| 618-8525 Japan Phone: (+81) 75-956-4148 | | | | | | ī l | |
| e-mail: md_tech_support@maxell.co.jp | | | Test number | Designation | Results | | |
| Web: https://www.maxell.co.jp | | | | | | | |
| | | | T-1 | Altitude Simulation | Pass | | |
| Description of cell or battery to include at a minimum: Lithium ion or | | | | | _ | | |
| Lithium metal cell or battery Mass; Watt-hour rating, or Lithium | | | T-2 | Thermal Test | Pass | | |
| content, Physical description of the cell/battery; and Model Number | | | T-3 | Vibration | Pass | | |
| Cell / battery Type : Lithium n | netal | | | | | | |
| , ,, | | | T-4 | Shock | Pass | | |
| Cell or Battery Cell (Single cell battery) | | | T-5 | External short circuit | Pass | | |
| Lithium content : 0.03g | | | T-6 | Impact / Crush | Pass | | |
| Cell or Battery Weight : 3.3g | | | | | | | |
| Physical description : Coin type | | | T-7 | Overcharge * | Not applicable | | |
| | | | T-8 | Forced Discharge | Pass | | |
| | | | * Only secondary battery with protection element | | | | |
| | | | | | T | | |
| Reference to assembled battery testing Reference to the revise | | | dition of the M | anual of Tests and | For air transport only: Does the cell or battery | | |
| requirements, if applicable(i.e. 38.3.3 (f) Criteria used and to am | | end | dments thereto | o, if any: | comply with the 30% State of Charge? | | |
| and 38.3.3 (g)) | | | | | | | |
| Not applicable Revision 6, Amendment | | | | | Not applicable | | |
| | | | | | | | |
| PRODUCT CLASSIFICATION FOR TRANSPORT(According to UN-DGP) | | | | | | | |
| UN Classification, | | | Proper Shipping Name: | | | | |
| UN3090 | | | Lithium Metal Batteries | | | | |
| Signature with name and title of signatory as an indication of the | | | | | | | |
| validity information provided. | | | This document remains valid as long as no changes, modifications or additions are made | | | | |
| Keisuke Kawabe / Senior Manager, MD Engineering Departme | | | to the model(s) described in this document, after being transported from a Manufacturer MAXELL, LTD. The model(s) has(have) been classified according to the applicable | | | | |
| Signature | | | transport regulations and the UN Manual of Tests and Criteria as of the date of the | | | | |
| K. Kawahe | | | certification. The model(s) must be packaged, labeled and documented according to country and other international regulations for transportation. | | | | |
| | | | , | | | | |
| Phone: (+81) 794-63-8054 e-mail: md_tech_support@maxell.co.jp | | | | | | | |
| " | | | | | | | |
| Date document was generated | | | | | | | |
| January 1, 2025 | | | | | | | |